

Liquid Level, Flow and Analytical products from Hayward Flow Control measure and control wide ranging Municipal, Commercial and Industrial processes.

## HLS Series Level Sensors



### KEY FEATURES

- Highly accurate hydrostatic pressure measurement, 0.25% accuracy full scale
- All CPVC housing with Al<sub>2</sub>O<sub>3</sub> (Alumina) sensing diaphragm
- 0-15 and 0-33 ft measurement range, 33 and 49 ft of PTFE coated cable std
- 10-35 VDC power required
- 4-20mA analog output signal
- 0-140°F temperature range
- MP10 desiccant tube and MP11 protection volume breather protection available
- Ceramic Sink Weights available for high specific gravity applications

## HLST Series Indicating Level Transmitter



### KEY FEATURES

- Dual Channel input and display (CH2 is RTD for temperature)
- Configurable, multi-color LCD display
- Simple, Intuitive menu makes set-up quick and easy
- NEMA 4X (IP65) Face, ¼ DIN chassis dimensions
- 100-240 VAC, 50-60 Hz power range std.
- Programmable dual relays and dual open collectors
- Optional HMCENC NEMA 4X Electrical Enclosure, ¼ DIN Cutout, 6 wire connectors

## HEX800 Series Flowmeter



### KEY FEATURES

- Insertion Electromagnetic Flow Sensor, 1 to 12"
- No moving parts, provides high reliability
- PVC Wetted Body, PVDF end cap, Hastelloy C Electrodes, EPDM o-ring, Cast AL Housing
- 0.28 to 20 FPS Velocity Range equals <1 GPM to 7000 gpm based on line diameter
- 150 psi @ 75F max, 32 to 130F
- +/- 1% Accuracy of Full Scale
- Blind 4-20mA output or integral (Built-in) Indicating Transmitter (HFT440)
- Full range of insertion fittings available

## HMC Series Analytical Indicating Transmitter



### KEY FEATURES

- Flow, pH/ORP and conductivity models available
- Common Features: Two Channel, process parameter + Temperature
- Dual, programmable 4-20mA outputs
- Dual, Programmable 5A/250V Relays, Dual Open Collectors
- ¼ DIN Chassis, NEMA 4X/IP65 Face
- 100-240V, 50-60 Hz power
- pH/ORP 0-14 pH or -1000 to +1000 mV ORP (HMCP100)
- Conductivity/Resistivity (HMCC100)
- Multi-parameter, 4-20mA input, configurable display (HMCM100)

## Z Series Solenoid Diaphragm Metering Pumps



### KEY FEATURES

- Highly chemically resistant wetted components
- Wall mountable with electrical connections, wetted end and controls all on pump face
- Analog and Digital Control interfaces
- Manual or analog signal pacing control
- Flow to 29 GPH and pressures to 232 psi
- ZRD Model features built-in pH/ORP controller
- ZRDPH100 pH and ZRDORP100 ORP industrial electrodes available for severe service
- Comes as a complete kit with mounting base, wall bracket, PVDF foot valve, PVDF injection valve and three 6 ft lengths of tubing
- Options: Multi-function Valve, Low level switch, Flow Sensor, PTFE Balls, EPDM

## Electrodes



### KEY FEATURES

- PRO15-10 pH, 10 ft wire, BNC, 3/4" MNPT process connection
- PRO25-10 ORP, 10 ft wire, BNC, 3/4" MNPT process connection
- ZRDPH100, Industrial pH, 10 foot wire standard, BNC, 3/4" MNPT connections on both ends
- ZRDORP100, Industrial ORP, 10 ft wire standard, BNC, 3/4" MNPT connections on both ends

## GA Series Pressure Gauge and Isolator

### KEY FEATURES

- Single faced
- 2-1/2" dial
- GFPP body with Guard
- 0-60, 0-100 and 0-160 psi scales



PP VERSION

## GDS Series Double Sided Pressure Gauge and Isolator

### KEY FEATURES

- Double-sided
- 2-1/2" dial
- GFPP body with guard
- 0-60, 0-100 and 0-160 psi scales



PVDF VERSION

## GD Series Digital LED Pressure Alarm

### KEY FEATURES

- 0-400 psi
- Digital LED display changes color (green to red) to indicate alarm condition
- Two 3A Relays
- 4-20 mA output
- 1/2" MNPT process connection



## GLD Series LED Pressure Gauge & Isolator

### KEY FEATURES

- 0-160 psi
- GFPP Body with Guard
- 4-20 mA output
- Open Collector output
- Bright LED display
- 1/2" FNPT process connection



PP VERSION



Hayward is a registered trademark of Hayward Industries, Inc.  
© 2017 Hayward Industries, Inc.

INSTFLYER

Contact Hayward Flow Control with questions:

USA: 1.888.429.4635 • Fax: 1.888.778.8410 • One Hayward Industrial Drive • Clemmons, NC 27012 • Email: hfcsales@hayward.com

Canada: 1.888.238.7665 • Fax: 1.905.829.3636 • 2880 Plymouth Drive • Oakville, ON L6H 5R4 • Email: hflowcanada@hayward.com

Visit us at: haywardflowcontrol.com