



FLOW CONTROL
One Hayward Industrial Drive
Clemmons, NC 27012 USA
Phone: 1-888-429-4635
Fax: 1-888-778-8410
www.HaywardFlowControl.com
HFCSales@Hayward.com

BFA SERIES THERMOPLASTIC BULKHEAD FITTINGS SPECIFICATIONS:

All BFA series thermoplastic bulkhead fittings shall be manufactured from PVC Type 1, Grade 1 (ASTM D1784, Cell Classification 12454), CPVC (ASTM D1784, Cell Classification 23447) or natural Polypropylene (ASTM D4101, Cell Classification 85580).

The gasket shall be EPDM or FPM for chemical service required. The valve body shall contain left-handed, buttress threads. Both the body flange and nut shall have hexagon-shaped outside-diameters to allow proper tool-gripping during installation.

The body flange shall be available as a standard size and large size (to provide better support for external equipment, ie shutoff valve). Connection configurations for PVC and CPVC bodies shall include: socket x socket (solvent weld), socket x threaded or threaded x threaded. PPL bodies shall be threaded x threaded connection only. The bulkhead fittings shall be available from 1/2"-6" sizes and shall be pressure-rated for 150 PSI at 70°F non-shock.

All Thermoplastic Bulkhead Fittings shall carry a three-year global warranty, shall be manufactured by Hayward® Flow Control and in the USA.



FLOW CONTROL
One Hayward Industrial Drive
Clemmons, NC 27012 USA
Phone: 1-888-429-4635
Fax: 1-888-778-8410
www.HaywardFlowControl.com
HFCSales@Hayward.com

BFAS THERMOPLASTIC BULKHEAD FITTINGS SPECIFICATIONS:

All BFAS series thermoplastic bulkhead fittings shall be manufactured from PVC Type 1, Grade 1 (ASTM D1784, Cell Classification 12454), CPVC (ASTM D1784, Cell Classification 23447) or natural Polypropylene (ASTM D4101, Cell Classification 85580). The gasket shall be EPDM or FPM for chemical service required.

The valve body shall contain left-handed, buttress threads. Both the body flange and nut shall have hexagon-shaped outside-diameters to allow proper tool-gripping during installation.

Connection configurations for PVC bodies shall include: socket x socket (solvent weld) and socket x threaded. CPVC bodies shall be socket x threaded connection only. PPL bodies shall be threaded x threaded connection only. The bulkhead fittings shall be available from 1/2"–4" sizes and shall be pressure-rated for 150 PSI at 70°F non-shock. All PVC/EPDM bulkhead fittings shall be NSF61 certified.

All Thermoplastic Bulkhead Fittings shall carry a three-year global warranty, shall be manufactured by Hayward® Flow Control and in the USA.