



FLOW CONTROL
One Hayward Industrial Drive
Clemmons, NC 27012 USA
Phone: 1-888-429-4635
Fax: 1-888-778-8410
www.HaywardFlowControl.com
HFCSales@Hayward.com

FLV SERIES THERMOPLASTIC FILTER VESSELS SPECIFICATIONS:

All thermoplastic filter vessels shall be manufactured from glass-filled Polypropylene conforming to ASTM D4101, Cell Classification 85580.

All O-rings shall be EPDM or FPM for chemical service required. Both single-length and double-length models shall be one-piece molded body, true union type design. Bodies shall contain (4) ports to accommodate in-line or loop-style flow patterns. Various end connection sizes and materials shall be available to accommodate installation requirements.

Bodies shall contain interrupted external cover thread for safety purposes. Each body shall have an integral mounting base. Covers shall contain vent valve which is protected by raised handles. Covers shall have an integral liquid-displacing dome on the underside of each cover. Cover-to-Body seal will be a facesal, NOT a piston-type seal.

The filter vessel shall accommodate both bag filtration and cartridge filtration (with use of a cartridge filter adapter kit). The internal basket, for bag filtration, shall be one-piece construction with vertical ribs to ease bag removal. And, a removable bag retainer ring, which will be locked in-place via a camlock handle integral to the basket, shall be used to ensure proper bag seating during operation. All filter vessels shall be pressure-rated for 150psi at 70°F non-shock. All Thermoplastic Filter Vessels shall carry a three-year global warranty, shall be manufactured by Hayward® Flow Control and in the USA.