

NEW PRODUCT PREVIEW

HXZSN 3A~3B Series Electric Actuators for Hazardous Locations

KEY FEATURES & BENEFITS

- Designed for use in hazardous locations
- Available from 880"lbs up thru 1770"lbs
- 120VAC operation standard, with 24VAC/VDC, 230VAC and 3 phase options available
- Units are equipped with two (2) volt-free Form A Auxiliary switches
- Anti-Condensate heater standard
- ISO5211 compliant mechanical mount w/ double-square female drive socket
- Two (2) 3/4" EMT ports for ease of field wiring
- NEMA 4/4X/IP66 Compliant
- Visual position indicator
- Clutchless Hand Wheel override standard
- Collapsible spinner handle
- Torque switches standard

Notice: Due to certification regulations and traceability requirements, this product is non-cancellable and non-returnable. Verify the product and certifications are approved for the project prior to ordering.



Ex d IIC T6 Gb, Ex tb IIIC T135 Db, IP66
Class I, Zone 1, AEx d IIC T6 Gb
Zone 21, AEx tb IIIC T135°C Db




TECHNICAL INFORMATION

ACTUATOR SPECIFICATIONS		HXZSN3A	HXZSN3B
Supply	Torque Output (in-lb / Nm)	880 / 100	1770 / 200
24VAC	Current Draw (Start / Run / LRA)	4.2A / 3.2A / 11.0A	4.2A / 3.2A / 11.0A
-	Speed (90°) DC-60Hz/50Hz, seconds	14 / 14	28 / 28
24VDC	Motor - 24V DC Perm Magnet 2 Pole Brush	25W	25W
120VAC	Current Draw (Start / Run / LRA)	1.2A / 0.9A / 1.5A	1.2A / 0.9A / 1.5A
	Speed (90°) 60Hz / 50Hz, seconds	16 / 19	33 / 39
	Motor - 120V Capacitor Run TENV	40W	40W
230VAC	Current Draw (Start / Run / LRA)	0.5A / 0.4A / 0.7A	0.5A / 0.4A / 0.7A
	Speed (90°) 60Hz / 50Hz, seconds	16 / 19	33 / 39
	Motor - 230V Capacitor Run TENV	40W	40W
All	Electrical Entry (2)	3/4" EMT w/ Polyamide dust cap	
	Control	On/Off, Proportional	
	Auxiliary Switch - End of Travel	(2) Form A Volt-Free, Rated 10A @ 250vac	
	Ambient Operating Range	-13°F to +149°F (-25°C to +65°C)	
	Humidity Range	0-95% RH	
	Altitude Limit	9850 ft / 3000 m	

HXZSN 3A~3B Series Electric Actuators for Hazardous Locations

TECHNICAL INFORMATION, *CONTINUED*

Ex d IIC T6 Gb, Ex tb IIIC T135 Db, IP66
Class I, Zone 1, AEx d IIC T6 Gb
Zone 21, AEx tb IIIC T135°C Db



MODEL	COVER REMOVAL CLEARANCE		HANDWHEEL		WEIGHT LBS/KG
	IN/MM	IN/MM	# TURNS FOR 90°		
HXZSN3A	8 / 200	4.79 / 122	12.5 turns 90°		30.8 / 14
HXZSN3B	8 / 200	4.79 / 122	12.5 turns 90°		30.8 / 14



Hayward is a registered trademark
of Hayward Industries, Inc.
© 2021 Hayward Industries, Inc.

NPP08211

USA: 1.888.429.4635 • Fax: 1.888.778.8410 • One Hayward Industrial Drive • Clemmons, NC 27012 • Email: hfcsales@hayward.com
Canada: 1.888.238.7665 • Fax: 1.905.829.3636 • 2880 Plymouth Drive • Oakville, ON L6H 5R4 • Email: hflowcanada@hayward.com
Visit us at: haywardflowcontrol.com