



FLOW CONTROL
One Hayward Industrial Drive
Clemmons, NC 27012 USA
Phone: 1-888-429-4635
Fax: 1-888-778-8410
www.HaywardFlowControl.com
HFCSales@Hayward.com

LA SERIES THERMOPLASTIC LATERAL 3-WAY BALL VALVES SPECIFICATIONS:

All thermoplastic lateral 3-way ball valves shall be manufactured from PVC Type 1, Grade 1 (ASTM D1784, Cell Classification 12454), or CPVC (ASTM D1784). All O-rings shall be EPDM or FPM for chemical service required. Seats shall be PTFE as standard. All sizes of valves shall be of true union design.

Different ball configurations shall be available (L-port (90-ball) and T-port (LA-ball)) to facilitate proper flow patterns required by engineer. Ball shall be installed into the body thru a side-port and secured via threaded seal retainer with PTFE seat. Stem shall contain double O-rings, and shall be blowoutproof design.

Body shall contain external tabs to accept an intermediate mounting kit if actuation is required. All 1/2" – 6" sizes shall be rated 150psi at 70°F non-shock. All sizes of ANSI 150 lb flanged valves shall be pressure-rated for 150psi at 70°F non-shock. All Thermoplastic Lateral 3-Way Ball Valves shall carry a three-year global warranty, shall be manufactured by Hayward® Flow Control and in the USA.