



UVH SERIES UV SANITIZERS - PVC

PVC Sch. 80 Construction with Type 316L SS Liner with 120, 240 and 480 kW range, supports up to 352 GPM flow rate. Available in “U” (Loop) configurations with 2” & 3” True Union Socket Ends, and 4” ANSI150 Flanged Ends. Low Pressure high output dual wavelength 185 nm & 254 nm amalgam lamps. UVH Series units are certified to NSF50. Includes Power Supply Unit.

PVC UVH Series					
RATED POWER (KW)	TYPE	END CONN.	FLOW PATH	PART NO.	LIST PRICE (USD)
120	Supplemental	2” SOC TU	U (Loop)	UVHS01201SSASU1	\$7,773.00
240		3” SOC TU		UVHS02401SSASU1	\$10,044.00
480		4” FLNG		UVHS04801SSAFU1	\$17,332.00

PVC UVH Series					
RATED POWER (KW)	TYPE	END CONN.	FLOW PATH	PART NO.	LIST PRICE (USD)
120	Secondary	2” SOC TU	U (Loop)	UVHS01201SCASU1	\$9,873.00
240		3” SOC TU		UVHS02401SCASU1	\$12,126.00
480		4” FLNG		UVHS04801SCAFU1	\$20,323.00